Amber Grain Chevron Oak



THICKNESS
14mm

WIDTH
90mm

LENGTH
510mm

WEAR LAYER
3mm

PACK SIZE
1.4688m²

PACK WEIGHT
15.16kg

25 YEAR
25-Year Warranty

Suitable for any domestic room, except bathrooms

Underfloor heating suitable

PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Brushed
WOOD SPECIES	Oak	FINISH	UV Oiled
PRODUCT ORIGIN	China	SHADE	Medium
BASE PLY	Poplar + Eucalyptus	COLOUR	Golden
CONSTRUCTION	Multi Ply	GRADE	Select
PATTERN	Chevron	JOINING	Tongue & Groove
EDGE PROFILE	4-sides 0.5mm	INSTALLATION METHOD	Nailed or Glued Down

TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	EN 717-1:2004-10	< LOD (216 h)* (class El)
Slip Rating	CNT/TS 15676:2007(D)	USRV22
Content of PCP	CEN/TR 14823:2004	PCP < 5 x 10-6n
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m³

CE